

chant™ escutcheons



400



401



402



402i



403



404



410



411




412



412i



413



414



420



421




422



422i



423



424

chant™ escutcheons

Oval Cylinder Escutcheons 400 / 410 / 420

Use with Legge 990 MF Series, Lockwood 3500 Series and Astra mortice locks (Australasia), and Union (UK).

Maximum door thickness with standard length cylinders	
400 escutcheon	56mm
410 and 420 escutcheons	52mm

Fastened with socket set screw on the underside.
To specify: 400 / 410 / 420 / Finish.

Turn Escutcheons 401 / 411 / 421

The turn mechanism is fastened to the door with screws, then concealed by either a 'screw-on' round style cover or a socket set screw on the underside of square style cover. Key bars to suit locks as detailed.

- A** – 6mm x 2mm bar for Legge 990 MF Series and Lockwood 3500 Series mortice locks. (Australasia)
- B** – 3/16" square spindle for Yale 4600, 8600 and 8700, and Schlage L Series mortice locks (USA)
- C** – 4.5mm square spindle
- D** – 7.0mm square spindle
- E** – 7.6mm square spindle
- F** – 8.0mm square spindle
- G** – 5.0mm square spindle
- H** – 6.0mm square spindle
- J** – 3/16" square spindle on the diamond (◇) for Accurate Locks (USA)

These spindles have a 2mm flat extension bar when ordered with Emergency Turns. Add suffix ET to order code e.g.
To specify: 401F/Finish/ET

To specify: 401 / 411 / 421 / A, B, etc / Finish

Emergency Turn Escutcheons 402 / 412 / 422

The turn mechanism is fastened to the door with screws, then concealed by either a 'screw-on' round style cover or a socket set screw on the underside of square style cover. Turn operated by key bar on 401 / 411 / 421 Turn Escutcheon above.

To specify: 402 / 412 / 422 / Finish

Emergency Turn / Indicator Escutcheons 402i / 412i / 422i

The turn mechanism is fastened to the door with screws, then concealed by either a 'screw-on' round style cover or a socket set screw on the underside of square style cover. Turn operated by key bar on 401 Turn Escutcheon above. Red and green colour indicator behind the turn button shows the lock status.

To specify: 402i / 412i / 422i / Finish

Profile Cylinder Escutcheons 403 / 413 / 423

Use with all profile cylinder mortice locks.

Maximum door thickness	
403 escutcheon with 5 pin cylinder	46mm
403 escutcheon with 6 pin cylinder	54mm
413 escutcheon with 5 pin cylinder	42mm
413 escutcheon with 6 pin cylinder	50mm

Fastened with socket set screw on the underside.
To specify: 403 / 413 / 423 / Finish

Pull / Turns 404A / 414A / 424A

For Legge 990 Series mortice locks.

Pull / Turns 404B / 414B / 424B

For SAB profile cylinder mortice locks.

For use on the inside of entrance doors to withdraw the latch bolt, when key entry is used on the outside. The turn base is securely fastened to an adaptor plate which is fixed to the side of the lock case prior to installation in the door.

To specify: 404A or B / 414A or B / 424A or B / Finish

Escutcheon Dimensions

Diameter or square	50mm
400 / 403 cylinder escutcheon projection	7mm
410/413/420/423 cylinder escutcheon projection	9mm
Turn escutcheon projection	30mm
Pull/Turn escutcheon projection	50mm

Finishes

Refer to *chant™ technical* 'Product Finishes'.

chant productions limited

chant™
in touch

8/136 marua rd, ellerslie
auckland, new zealand
tel: + 64 9 526 4048
fax: + 64 9 526 4049
email: sales@chantproductions.co.nz
internet: www.chantproductions.co.nz

issue 09/03

©chant productions ltd, 2003