



Escutcheons



PM100 Cylinder Escutcheon

Use with Legge 990 MF Series, Lockwood 3500 Series and Astra mortice locks (Australasia). Requires minimum lock cylinder projection beyond the door surface of 14mm. Maximum door thickness with standard length cylinders is 46mm. For thicker doors use extended cylinders or PM103 Cylinder Escutcheon.

For Union 2041 mortice lock with standard double cylinder, maximum door thickness is 35mm, or 53mm with extended double cylinder.

Fastened with socket setscrew on the underside.

To specify: PM100/Finish.



PM101 Turn Escutcheon

Turn mechanism fastened to door with screws, then concealed by 'screw-on' cover. Key bars to suit locks as detailed.

A – 6mm x 2mm bar for Legge 990 MF Series and Lockwood 3500 Series mortice locks. (Australasia)

B – 3/16" square spindle for Yale 4600, 8600 and 8700, and Schlage L Series mortice locks (USA)

C – 4.5mm square spindle

D – 7.0mm square spindle

E – 7.6mm square spindle

F – 8.0mm square spindle

G – 5.0mm square spindle

H – 6.0mm square spindle

These spindles have a 2mm flat extension bar when ordered with PM102 Emergency Turn. Add suffix ET to order code e.g. *To specify:* PM101/Finish/ET


To specify: PM101/A, B, etc/Finish



PM102 Emergency Turn Escutcheon

Turn mechanism fastened to door with screws, then concealed by 'screw-on' cover. Turn operated by key bar on PM101 Turn Escutcheon above.

To specify: PM102/Finish



PM102I Emergency Turn / Indicator Escutcheon

Turn mechanism fastened to door with screws, then concealed by 'screw-on' cover. Turn operated by key bar on PM101 Turn Escutcheon above.

Red and green colour indicator behind the turn button shows the lock status.

To specify: PM102I / Finish




PM103 Cylinder Escutcheon

Use with Union 2241 mortice lock where there is insufficient distance between the cylinder and lever rose for the PM100 Escutcheon. Doors thicker than 50mm will require an extended cylinder.

Fastened with socket setscrew on the underside.


To specify: PM103/Finish



PM104 Profile Cylinder Escutcheon

Use with all Profile Cylinders, particularly with locks where there is insufficient distance between cylinder and lever rose to use the PM105 Cylinder Escutcheon.


Fastened with socket setscrew on the underside.
To specify: PM104/Finish



PM105 Profile Cylinder Escutcheon


Use with all Profile Cylinders. Radiused edge of this escutcheon complement the domed lever handle rose.

To specify: PM105/Finish




PM105A Thumb Turn

8mm Ø bore to suit CISA and Corbin Profile Cylinder Barrels.
To specify: PM105A/Finish




PM105B Thumb Turn

9mm Ø bore to suit SAB Profile Cylinder Barrel.
To specify: PM105B/Finish





PM105C Thumb Turn

10mm Ø bore to suit GSV Profile Cylinder Barrel.
To specify: PM105C/Finish




PM105D Thumb Turn

10mm Ø bore to suit CES Profile Cylinder Barrel.
To specify: PM105D/Finish



PM106A and PM106B Recessed Cylinder Rings

PM106 A $x = 5\text{mm}$ (3/16")
 PM106 B $x = 6.5\text{mm}$ (1/4")
 For Yale, Schlage etc cylinders.
To specify: PM106A or B/Finish



PM107A Pull / Turn For Legge 990 Series Mortice Locks

PM107B Pull / Turn For SAB Profile Cylinder Mortice Locks

For use on the inside of entrance doors to withdraw the latch bolt, when key entry is used on the outside.
 The turn base is securely fastened to an adaptor plate which is fixed to the side of the lock case prior to installation in the door.
To specify: PM107A or B/Finish

PM109 Privacy Bolt / Turn Assembly

This includes a 60mm backset privacy bolt, PM101 Turn Escutcheon and PM102 Emergency Turn Escutcheon.
To specify: PM109/Finish

PM109R Privacy Bolt / Turn Assembly

As above with kit for Rebated doors.
To specify: PM109R/Finish